

技术资料书

KAPTON®聚酰亚胺胶带

产品编号 : 1K7178

(阻燃性)

P. LEO & CO LTD

P.O. Box 175 Fo Tan, Shatin, Hong Kong.

Telephone : (852) 2604-8222 * Facsimile : (852) 2693-2093

E-mail : sales@pleo.com * Web Site : <http://www.pleo.com>



UL FILE #E126174

说明 : 1K7178 KAPTON®聚酰亚胺胶带是在 0.025mm 厚的 KAPTON 聚酰亚胺薄膜覆涂一层压敏丙烯酸酯胶粘剂而成; 材质坚韧, 防刺穿。本产品符合 UL510 阻燃的要求。

用途 : 耐温等级 155°C, 适用各种电气产品。

技术数据 :	性能	单位	规格
	颜色	-	琥珀色 (茶色)
	总厚度	mm (mil)	0.063 ± 0.006 (2.5)
	基材厚度	mm (mil)	0.025 (1)
	拉伸强度	kg/25mm (lb/in)	13.6 (29)
	伸长率	%	50
	黏着力	kg/25mm (oz/in)	0.7 (24)
	击穿电压	kV	6.0
	温度等级	°C	155

包装标准 : 每卷长 33M、宽 630mm, 卷心直径 3 英寸

保存期限 : 六个月 (温度: 23°C 湿度: 65%)

*KAPTON 是美国杜邦公司的注册商标

Important Notice to Purchase

All Statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury loss or damage direct or consequential arising out of the use of or *he inability to use the product. Before using users shall determine the suitability of the product for their intended uses and users assume all risk and liability whatsoever in connection there with.

No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of Seller and manufacturer.

仅供参考, 如与英文版有歧异之处, 一切内容以英文版为准。



HALOGEN
FREE



Copyright © P.LEO 2009 Rev. 4