


# 技术资料书

## 聚酰亚胺胶带

产品编号 : 1KPST  
(阻燃性)

### P. LEO & CO LTD

P.O. Box 175 Fo Tan, Shatin, Hong Kong.  
Telephone : (852) 2604-8222 \* Facsimile : (852) 2693-2093  
E-mail : sales@pleo.com \* Web Site : <http://www.pleo.com>



UL FILE #E126174

说明 : 1KPST 聚酰亚胺胶带是在 0.025mm 厚的聚酰亚胺薄膜涂覆一层热固性压敏硅胶粘剂而成。具有耐高温物理和电气性能。本产品符合 UL 510 阻燃要求。

应用 : 适用于变压器、线圈、扁平电缆、连接器、线束包裹、电容器及发电机上；也适用于线路板焊锡及波峰焊及保护金手指部位。它是 H 级的绝缘材料。

性能	单位	规格
颜色	-	琥珀色 (茶色)
总厚度	mm	0.060 ± 0.003
拉伸强度	kg/25mm	11
伸长率	%	50
黏着力	kg/25mm	0.5
回卷力	kg/25mm	0.8
击穿电压	kV	5
绝缘强度	ohm	1x10 <sup>12</sup>
耐热等级	°C	180
腐蚀系数	-	1

测试方法 : 根据 ASTM 标准测试

保存期限 : 六个月 (温度: 73F 湿度: 65%)

包装标准 : 每卷长 33M, 宽 500mm, 卷心直径 3 英寸

#### **Important Notice to Purchase**

All Statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury loss or damage direct or consequential arising out of the use of or \*he inability to use the product. Before using users shall determine the suitability of the product for their intended uses and users assume all risk and liability whatsoever in connection there with.

No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of Seller and manufacturer.

仅供参考, 如与英文版有歧异之处, 一切内容以英文版为准。

