


技术资料书

芳香聚酰胺纸胶带 产品编号 : 1N008F

P. LEO & CO LTD

P.O. Box 175 Fo Tan, Shatin, Hong Kong.
Telephone : (852) 2604-8222 * Facsimile : (852) 2693-2093
E-mail : sales@pleo.com * Web Site : http://www.pleo.com



UL FILE #E126174

说明 : 1N008F 芳香聚酰胺纸胶带是在 2 mil (0.05mm)厚的 NOMEX®纸涂覆一层丙炔酸酯胶粘剂而成，具有良好的抗溶性和阻燃性。

用途 : 适用于变压器、电动马达、线圈包裹及电容器上，在浸渍中具有良好的吸漆性。最高可应用于 H 级的绝缘系统中。

性能	单位	规格
颜色	-	白色
总厚度	mm (mil)	0.09 ± 0.01 (3.6)
基材厚度	mm (mil)	0.05 (2)
拉伸强度	kg/25mm (lb/in)	10 (22)
伸长率	%	10
黏着力	kg/25mm (oz/in)	0.5 (17.6)
击穿电压	kV	2.5
耐热等级	°C	155

*NOMEX 是美国杜邦公司的注册商标

测试方法 : 根据 ASTM 标准测试

保存期限 : 二个月 (温度: 73F 湿度: 65%)

包装标准 : 每卷长 30M, 宽 440mm, 卷心直径 3 英寸

Important Notice to Purchase

All Statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury loss or damage direct or consequential arising out of the use of or *he inability to use the product. Before using users shall determine the suitability of the product for their intended uses and users assume all risk and liability whatsoever in connection there with.

No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of Seller and manufacturer.

仅供参考, 如与英文版有歧异之处, 一切内容以英文版为准。

