

# 技術資料書

## 無紡布擋牆膠帶 產品編號:1H860T

### P. LEO & CO LTD

P.O. Box 175 Fo Tan, Shatin, Hong Kong.  
Telephone : (852) 2604-8222 \* Facsimile : (852) 2693-2093  
E-mail : sales@pleo.com \* Web Site : <http://www.pleo.com>



UL FILE #E126174

**說明：** 1H860T是1H860的增厚版，在聚酯薄膜基材上貼合無紡布，再在無紡布上塗覆一層性能優良的丙烯酸膠粘劑而成。取得UL認證，耐溫等級130℃。PLC=0 CTI等級I。

**特點/優點：** 良好的黏著力和耐溶劑性，使用方便，適用於人工作業或機器操作上。

**應用：** 主要應用於變壓器的擋牆及層間絕緣

技術資料：	性能	單位	規格
	總厚度	mm (mil)	0.43±0.03 (17.2)
	拉伸強度	kg/25mm (lb/in)	13 (28)
	伸長率	%	70
	黏著力	kg/25mm (oz/in)	1 (35)
	擊穿電壓	kV	6
	耐熱等級	°C	130

**測試方法：** 根據 ASTM 標準測試

**保存期限：** 6 個月（溫度：23℃、濕度：65%）

**包裝標準：** 每卷長 30M，寬 970mm，卷心直徑 3 英寸

#### **Important Notice to Purchase**

All Statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury loss or damage direct or consequential arising out of the use of or "he inability to use the product. Before using users shall determine the suitability of the product for their intended uses and users assume all risk and liability whatsoever in connection there with.

No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of Seller and manufacturer.

以上僅供參考，如與英文版有歧異之處，一切內容以英文版為準



Copyright © P. LEO 2009 Rev. 2