


技術資料書

聚酰亞胺膠帶 產品編號:1K125 (阻燃性)

P. LEO & CO LTD

P.O. Box 175 Fo Tan, Shatin, Hong Kong.
Telephone : (852) 2604-8222 * Facsimile : (852) 2693-2093
E-mail : sales@pleo.com * Web Site : http://www.pleo.com



UL FILE #E126174

說明： 1K125 聚酰亞胺膠帶是在 0.0125mm 厚的聚酰亞胺薄膜塗覆一層高溫的熱固化矽膠壓敏粘合劑而成。出色的耐高溫及電氣性能，本產品符合 UL510 阻燃要求。

用途： 適用於變壓器、線圈、扁平電纜、連接器、線束包裹、電容器及發電機上；也適用於線路焊錫及波峰焊及保護金手指部位。它是 R 級絕緣材料。

技術資料：	性 能	單 位	規 格
	顏色	—	琥珀色 (茶色)
	總厚度	mm	0.038 ± 0.003
	拉伸強度	kg/25mm	5
	伸長率	%	50
	黏著力	kg/25mm	0.3
	回卷力	kg/25mm	0.8
	擊穿電壓	kV	4
	絕緣強度	ohm	1×10^{12}
	溫度等級	°C	220
	腐蝕係數	—	1

測試方法： 根據 ASTM 標準測試

保存期限： 6 個月 (溫度: 73°F、濕度: 65%)

包裝標準： 每卷長 33M, 寬 500mm, 卷心直徑 3 英寸

Important Notice to Purchase

All Statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury loss or damage direct or consequential arising out of the use of or "he inability to use the product. Before using users shall determine the suitability of the product for their intended uses and users assume all risk and liability whatsoever in connection there with.

No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of Seller and manufacturer.

以上僅供參考，如與英文版有歧異之處，一切內容以英文版為準



Copyright © P. LEO 2007 Rev. 2